

AVICENA COMPUTERS

B-dul Stefan cel Mare nr. 8-10

Tel: 0232/217.611

0332/407.784

0752/069.909

E-mail: office@avicena.ro

Web: www.avicena.ro

02 Septembrie 2010

OFERTĂ COMPONENTE

Preturile sunt exprimate in lei si contin TVA.

| HARD DISK-URI | FORMATARE GRATUITĂ ! | |
|---|----------------------|-------|
| SEAGATE 160 GB SATA II, 7200, 8M | | 172 |
| SEAGATE 250 GB SATAII, 7200rpm, 8M | | 177 |
| SEAGATE 320 GB SATAII, 7200rpm, 16M | | 190 |
| SEAGATE 500 GB SATAII, 7200, 16MB | | 195 |
| SEAGATE 750 GB SATAII, 7200.11, 32MB | | 311 |
| SEAGATE 1TB SATAII, 7200.12 32MB | | 323 |
| SEAGATE 1.5TB SATAII, 7200.11 32MB | | 445 |
| WD 160 GB, ATA100, 8M, 7200rpm WD1600JB | | 212 |
| WD 160 GB, SATA II, 8M, 7200rpm WD1600JS | | 171 |
| WD 250 GB, ATA100, 8M, 7200rpm WD2500JB | | 271 |
| WD 250 GB, SATAII, 16M, 7200rpm WD2500KS | | 187 |
| WD 320 GB, ATA100, 8M, 7200rpm WD3200JB | | 289 |
| WD 320 GB, SATAII, 16M, 7200rpm WD3200KS | | 191 |
| WD 500GB, SATAII, 16M, 7200rpm WD5000KS | | 196 |
| WD 640GB, SATAII, 32M, 7200rpm WD6400AADS | | 230 |
| WD 750GB, SATAII, 32MB, 7200rpm WD7500AADS | | 371 |
| WD 1TB Caviar Green, Serial ATA2, 7200 rpm, 64MB WD10EARS | | 202 |
| WD 2TB, SATAII, 64MB, 7200rpm WD20EARS | | 537 |
| WD 250 GB, Extern Passport Essential 2.5", 5400rpm, 8MB, 12ms, negru | | 289 |
| WD 320 GB, Extern Passport Essential 2.5", 5400rpm, 8MB, 12ms, negru | | 305 |
| WD 500 GB, Extern My Book Essential - Apollo - 3.5", Black, USB 2.0 WDBAAF5000EBK | | 347 |
| WD 1TB, Extern, My Book Essential - Apollo - 3.5", Black, USB 2.0 WDBAAF0010HBK | | 442 |
| SAMSUNG 160GB/7200 SATAII 8MB | | 171 |
| SAMSUNG 250GB/7200 SATAII 16MB | | 180 |
| SAMSUNG 320GB/7200 SATAII 16M | | 185 |
| SAMSUNG 500GB/7200 SATAII, 16MB | | 191 |
| SAMSUNG 640GB/7200 SATAII, 16MB | | 225 |
| SAMSUNG 750GB/7200 SATAII, 32MB | | 275 |
| SAMSUNG 1TB/7200 SATAII, 32MB | | 311 |
| SAMSUNG 160GB 2.5" Notebook HDD, SATA, 5400rpm, 8MB | | 171 |
| SAMSUNG 250GB 2.5" Notebook HDD, SATA, 5400rpm, 8MB TuMR/PMR | | 180 |
| SAMSUNG 320GB 2.5" Notebook HDD, SATA2, 5400rpm, 8MB, TuMR/PMR | | 203 |
| SAMSUNG 160GB 2.5" Portable drive, USB2.0, Stylish Wine Red, Retail package (S2 F) | | 225 |
| SAMSUNG 250GB 2.5" Portable drive, USB2.0, Stylish Piano Black, Retail package (S2 F) | | 270 |
| SAMSUNG 320GB 2.5" Portable drive, USB2.0, Stylish Piano Black, Retail package (S2 F) | | 297 |
| SAMSUNG 500GB 2.5" Portable drive, USB2.0, Stylish Piano Black, Retail package (S2 F) | | 392 |
| SSD | | |
| Kingston X25-V SSDNow V Series 30GB SATA 2.5IN internal SSD | | 411 |
| Kingston X25-V SSDNow V Series 64GB SATA 2.5IN internal SSD | | 661 |
| Kingston X25-V SSDNow V+ Series 128GB SATA II 2.5IN internal SSD | | 1,372 |
| A-DATA SSD S-ATA II (R/W - 250/190MB) 2.5" 32GB MLC 2 ani SSD 5592 32GB | | 455 |
| A-DATA SSD S-ATA II (R/W - 163/97MB) 2.5" 64GB MLC 2 ani SSD 391 64GB | | 596 |
| A-DATA SSD S-ATA II (R/W - 163/97MB) 2.5" 128GB MLC 2 ani SSD 391 128GB | | 1,007 |
| PROCESOARE | | |
| Sempron LE-140 2.7GHz AM3 1MB (45W) BOX | | 165 |
| Athlon II X2 240 2.8GHz AM3 2MB 65W | | 280 |
| Athlon II X2 245 2.9GHz AM3 2MB 65W | | 291 |
| Athlon II X2 250 3.0GHz AM3 2MB 65W | | 301 |
| Athlon II X3 440 3.0GHz 1.5MB 95W AM3 box | | 363 |
| Athlon II X3 445 3.1GHz AM3 1.5MB 95W | | 384 |
| Athlon II X4 635 2.9 GHz AM3 2MB 95W box | | 493 |
| Athlon II X4 640 3.0GHz AM3 2MB 95W | | 514 |
| Phenom II X2 550 3.1GHz AM3 7MB 80W Black Edition | | 425 |
| Phenom II X2 555 3.2GHz AM3 7MB 80W Black Edition | | 451 |
| Phenom II X4 945 3.0GHz AM3 8MB 95W | | 670 |
| Phenom II X6 1055T 3.3GHz 9MB 125W AM3 box | | 1,011 |
| INTEL Celeron Dual Core E3300 2.5 GHz FSB800 1M Socket 775 45nm BOX | | 221 |
| INTEL Celeron Dual Core E3400 2.6 GHz FSB800 1M Socket 775 45nm BOX | | 257 |
| Pentium Dual core E5400 2,7 GHz FSB 800 2MB L2 45nm Socket 775 BOX | | 298 |
| Pentium Dual Core E5500 2,8GHz FSB800 2MB 5775 45nm | | 334 |
| Pentium Dual core E6500 2,93 GHz FSB 1066 2MB L2 45nm Socket 775 BOX | | 356 |
| Pentium Dual Core G6950 2.8MHz 3MB LGA1156 BOX | | 442 |
| Conroe Intel Core 2 Duo E7500 2,93 GHz FSB1066 3MB L2 45nm Socket 775 BOX | | 580 |
| Conroe Intel Core 2 Duo E8400 3.0 GHz FSB1333 6MB L2 45nm Socket 775 BOX | | 826 |
| Conroe Intel Core 2 Duo E8500 3,16 GHz FSB1333 6MB L2 45nm Socket 775 BOX | | 925 |
| Conroe Intel Core 2 Duo E8600 3,33 GHz FSB1333 6MB L2 45nm Socket 775 BOX | | 1,322 |
| Core i3 i3-530 2.93GHz 4MB LGA1156 BOX | | 514 |
| Core i5 i5-650 3.20GHz 4MB LGA1156 BOX | | 850 |
| Core i7 i7-930 2.80GHz (4.8 GT/sec, 8MB, S1366) BOX | | 1,315 |
| Core™2 Quad Processor Q8400 2.66 GHz FSB1333 4MB L2 45nm Socket 775 BOX | | 828 |
| Core™2 Quad Processor Q9505 2,830 GHz FSB1333 6MB L2 45nm Socket 775 BOX | | 1,089 |

| PLACI DE BAZA PENTRU PROCESOARE AMD | | |
|--|--|-----|
| GIGABYTE | | |
| MA74GM-S2H AMD RS740, s.AM2(AM3 CPU support), video, HDMI, GbLAN, 6xSATA2, 1xPATA, 1xPCI-E(x16), 1xPCI-E(x1), | | 230 |
| M52L-S3P nForce 520LE, s.AM2, LAN, 2xSATA 2, 1xPCI-E(x16), 2xPCI-E(x1), 4xPCI, Raid 0, 1, 4xDDR2 800, 8xUSB, ATX, a | | 225 |
| M720-US3 NV 720d, s.AM2, LAN, 6xSATA 2, 1xPCI-E(x16), 2xPCI-E(x1), 4xPCI, Raid 0, 1, 0+1, 5, 4xDDR2 1066, ATX, audio | | 271 |
| MA770T-UD3 AMD 770, s.AM3, 1xGbLAN, 6xSATA 2, 1xPCI-E(x16), 4xPCI-E(x1), 2xPCI, Raid 0, 1, 0+1, JBOD, 1xIDE, 4xDD | | 335 |
| MA785GMT-UD2H AMD 785G, s.AM3, video, DX10.1, HDMI, GbLAN, 6xSATA 2.0, 1xPATA, 1xPCI-E 2.0(x16), | | 356 |
| 1xPCI-E(x1), 2xPCI, RAID 0, 1, 0+1, JBOD, 4xDDR3 1333, uATX, audio 8ch (ALC889A/Dolby), UpTo 12xUSB 2.0, Up to 2xI | | |
| ASROCK | | |
| K7S41GX SIS 741GX, Ska, FSB 333Mhz, 2*DDR333, ATA133, 1*AGP 8x/2*PCI, AMR, SB, VGA Real 256E 3D Gfx. Max. 6 | | 249 |
| K8NF3-VSTA nForce3 250, Skt 754, HT 1600MT/s, 2*DDR 400 max 2GB, 1*AGP8x/4*PCI, 8CH AC97, LAN Realtek PHY, 2* | | 223 |
| 939A785GMH/128M AMD 785G +SB710, Skt 939, FSB1000, 4*DDR400 DualCh max 4GB, 1*PCIE16/1*PCIE12/2*PCI, ATI C | | 337 |
| ALIVEXFIRE-ESATA2 ATI Radeon XPRESS 1600 CrossFire(RD480), Skt AM2+/ AM2, HT 2000MT/s, 4*DDR2 800 DualCh max | | 203 |
| ASUS | | |
| M4A78L-M-LE AMD 760G(780L)/SB710, Sk AM2/AM2+ HT3 5200/4800, 2*DDR2-1200(O.C.)/1066/800/667 DualCh ECC, | | 260 |
| VGA on board (max 1024MB Sh), 1*PCIE2.0x16(Hybrid CFx support)/1*PCIE1/2*PCI, 1*D-Sub, ATA133*/SATA 3Gb/s*6(R | | |
| M2N68-PLUS nForce630a, Sk AM2/AM2+ HT 2000/1600, 2*DDR2-1066(O.C.)/800/667 Dual Ch ECC, 1*PCIE | | 244 |
| 2.0x16/4*PCI/2*PCIE1, ATA133*/SATA 3Gb/s*4(RAID 0, 1, 0+1, JBOD), Sound 6-CH(HD) ALIC662, GbLAN PHY, 10*USB, A | | |
| M4N78-SE nForce 720D (MCP78D), Sk AM2/AM2+ HT3 5200/4800, 2*DDR2-1066/800/667 Dual Ch ECC, | | 248 |
| 1*PCIE2.0x16/3*PCI/2*PCIE1, ATA133*/SATA 3Gb/s*4(RAID 0, 1, 0+1, 5, JBOD), Sound 6-CH(HD) ALIC662, GbLAN Reale | | |
| M4N68T nForce630a, Sk AM3 HT 2000/1600, 4*DDR3-1800(O.C.)/1600(O.C.)/1333/1066 Dual Ch ECC, 1*PCIE2.0x16/ | | 260 |
| 4*PCI/2*PCIE1, ATA133*/SATA 3Gb/s*4(RAID 0, 1, 0+1, 5, JBOD), Sound 8-CH(HD) VIA VT1708S, GbLAN PHY, 10*USB, A | | |
| M4N68T-M nForce630a/GeForce 7025, Sk AM3 HT 2000/1600, 2*DDR3-1800(O.C.)/1600(O.C.)/1333/1066 Dual Ch | | 243 |
| ECC, VGA on board (max 256MB Sh), 1*PCIE2.0x16/2*PCI/1*PCIE1, ATA133*/SATA 3Gb/s*4(RAID 0, 1, 0+1, 5, JBOD), S | | |
| M4A785T-M AMD 785G/SB710, Sk AM3 HT3 5200/4800, 4*DDR3-1800(O.C.)/1600(O.C.)/1333/1066 DualCh ECC, | | 363 |
| VGA on board (max 512MB Sh), 1*PCIE2.0x16(Hybrid CrossFireX support)/2*PCI/1*PCIE1, 1*D-Sub+1*HDMI, ATA13 | | |
| M4A77T AMD 770/SB710, Sk AM3 HT3 5200/4800, 4*DDR3-1800(O.C.)/1600(O.C.)/1333/1066 DualCh ECC, 1*PCIE2.0x16/3* | | 394 |
| PCI/2*PCIE1, ATA133*/SATA 3Gb/s*6(RAID 0, 1, 10, JBOD), Sound8-CH(HD) VIA VT1708S, 1*GbLAN Realtek PCIe, 12*US | | |
| M4A79XTD.EVO ATI 790X/SB750, Sk AM3 HT3 5200/4800, 4*DDR3-1800(O.C.)/1600(O.C.)/1333/1066 DualCh ECC, | | 477 |
| 2*PCIE2.0x16(1 x16 or dual x8)(CrossFireX @dual x8; up to 4 GPUs)/2*PCI/2*PCIE1, ATA133*/SATA 3Gb/s*5(RAID 0, 1, | | |
| M4A89TD-PRO ATI 890FX/SB850, Sk AM3 HT3 5200/4800, 4*DDR3-2000(O.C.)/1600(O.C.)/1333/1066 DualCh ECC, 2*PCIE2.0x | | 855 |
| (dual x16)/1*PCIE4/1*PCIE1/2*PCI, SATA 6Gb/s*6(RAID0, 1, 5, 10), Extra storage JMB361: ATA133*/SATA 3Gb/s*1 (or | | |
| PLACI DE BAZA PENTRU PROCESOARE INTEL | | |
| GIGABYTE | | |
| G31M-ES2L Intel G31, s.775, FSB 1333, video, LAN, 4xSATA 2, 1xPCI-E(x16), 1xPCI-E(x1), 2xPCI, 2xDDRII 800, mATX, au | | 203 |
| P41-E53G Intel G41, s.775, FSB 1333, GbLAN, 4x SATA 2, 1xPATA, 1xPCI-E(x16), 3xPCI-E(x1), 3xPCI, 2xDDRII 800 DC, AT | | 260 |
| P43-E53G Intel P43, s.775, FSB 1333, GbLAN, 6xSATA 2, 1xPATA, 1xPCI-E(x16), 1xPCI-E(x1), 5xPCI, 4xDDR2 1200, ATX, | | 332 |
| EP45T-UD3LR Intel P45, s.775, FSB 1600, 1xLAN, 6xSATA 2, 1xPCI-E(x16), 3xPCI-E(x1), 3xPCI, Raid 0, 1, 5, 10, | | 480 |
| 4xDDRIII 1600 Dual Channel, ATX, audio 8ch, 12xUSB, | | |
| EQ45M-S2 Intel Q45, s.775, FSB 1333, 1xGbLAN, video VGA+DVI, 1xPCI-E(x16), 1xPCI-E(x1), 2xPCI, Raid | | 459 |
| 0, 1, 5, 10, 4xDDRII 800 DC, uATX, audio 8ch, Up to 12xUSB | | |
| X58A-UD3R Intel X58, s.1366, QPI 6.4GT/s, 1xGbELAN, 2xSATA 3.0, 8xSATA 2, 4xPCI-E(x16), 2xPCI-E(x1), 1xPCI, | | 978 |
| RAID0, 1, 5, 10, 6xDDR3 2000, ATX, audio 8ch, 2xUSB2.0, 10xUSB2.0, 2xeSATA, 3x1394a | | |
| H55M-S2 Intel@ H55 Express, s.1156, QPI 6.4GT/s, video(D-SUB), 6*S-ATA2, 1*PCI-E x16, 1*PCI-E x1, 2*PCI, 2*DDR3 1333 | | 362 |
| ASUS | | |
| P5KPL-AM/EPU INTEL G31/ICH7, LGA 775 1600(O.C.)/1333/1066/800MHz, 2*DDR2-1066(O.C.)/800/667 Dual Ch, | | 199 |
| VGA On board (max 256MB Share), 1*PCIE16/2*PCI/1*PCIE1, ATA100*/SATA II*4, Audio 8-CH(HD) VIA VT1708B, GbLA | | |
| P5KPL-SE INTEL G31/ICH7, LGA 775 1600(O.C.)/1333/1066/800MHz, 2*DDR2-1066(O.C.)/800/667 Dual Ch, | | 270 |
| 1*PCIE16/3*PCIE1/3*PCI, ATA100*/SATA 3Gb/s*4, Audio 6-CH(HD) ALC662, S/PDIF (Optical out), GbLAN Realtek PCIe, | | |
| P5P41D INTEL G41/ICH7, LGA 775 1333/1066/800MHz, 4*DDR2-1066(O.C.)/800/667 Dual Ch, 1*PCIE16/3*PCI/ | | 315 |
| 2*PCIE1, ATA100*/SATA 3Gb/s*4, Sound 8CH HD ALC 887, S/PDIF(Optical out), GbLAN Atheros PCIe, 8*USB2.0, ATX | | |
| P5QL/EPU INTEL P43/ICH10, LGA 775 1600(O.C.)/1333/1066/800MHz, 4*DDR2-1066/800/667 D Ch, 1*PCIE2.0x16/ | | 353 |
| 3*PCI/2*PCIE1, SATA 3Gb/s*6, Extra storage Controller Marvell 88SE6102: ATA133*1, Sound 8-CH(HD) VIA VT1708B/S, | | |
| P5N-D nForce 750i SLI(C72P)/MCP51, LGA 775 1333/1066/800/533MHz, 4*DDR2-800/667/533 Dual Ch, | | 447 |
| 2*PCIE2.0x16(SLI x8+x8)/2*PCIE1/2PCI, ATA133*/SATA 3Gb/s*4(RAID 0, 1, 0+1, 5, JBOD), Sound 8-CH(HD) ALC883, S | | |
| P5Q-DELUXE INTEL P45/ICH10R, LGA 775 1600/1333/1066/800MHz, 4*DDR2-1200/1066/800/667 Dual Ch, | | 649 |
| 2*PCIE2.0x16/1*PCIE16/2*PCI/2*PCIE1, SATA 3Gb/s*6(RAID 0, 1, 5, 10), Extra storage Controller Sil5723, Marvell 88SE | | |
| P6T-SE INTEL X58/ICH10R, LGA 1366 QPI Up to 6.4GT/s, 6*DDR3-2000(O.C.)/1800(O.C.)/1600(O.C.)/1333/1066 | | 934 |
| Triple Ch, 3*PCIE2.0x16 (CrossFireX @x16/x16/x4)/1*PCIE1/2*PCI, SATA 3Gb/s*6(RAID 0, 1, 5, 10), | | |
| Extra storage Controller Marvell JMB363: ATA133*/SATA 3Gb/s*1 (one is eSATA), Sound 8-CH(HD) ALIC1200, S/PDIF (| | |
| P7H55-M-PRO INTEL H55, LGA 1156, 4*DDR3-2133(O.C.)/1333/1066 Dual Ch, VGA on board (max 1748MB Sh), 1*PCIE2.0x1 | | 477 |
| 1*PCIE1/2*PCI, 1*D-Sub+1*HDMI, SATA 3Gb/s*6, Extra storage Controller JMB368: ATA133*1, Express Gate, Up | | |
| P7P55D INTEL P55, LGA 1156 4*DDR3-2133(O.C.)/1600/1333/1066 Dual Ch, 1*PCIE2.0x16 (single at x16)+ | | 623 |
| 1*PCIE2.0x16@x4 mode, 2.5GT/s)CrossFire @x16/x4/2*PCIE1/3*PCI, SATA 3Gb/s*6(RAID 0, 1, 5, 10), Extra storage Con | | |
| AT5NM10-INTEL NM10 (CPU ATOM D510 Dual Core on board), 2 DDR2 - 800/667 Single Channel max 4GB, 1xPCI, | | 411 |
| VGA on board Intel Graphics Atom D510 (max sh 256MB), 2 xSATA 3 Gb/s, GLAN, 6CH Audio , 8 USB2.0, mini ITX | | |
| ASROCK | | |
| P4I65G INTEL 865G + ICH5, SK 478, FSB 800Mhz, 2*DDR400 Dual Channel, 2*ATA 100, 2*SATA, 1*A.G.I.8x | | 280 |
| (AGP8x/4x)/3*PCI/1*AMR, VGA on board (max shared 96MB), 6ch SB, Lan, mATX, USB2.0, Supports Untied Overclocking | | |
| 4COREDUAL-SATA2R2.0 VIA PT880Pro/Ultra, Skt 775, FSB 1066MHz, 2*DDR2 667/2*DDR 400 Dual Ch | | 291 |
| max 2GB, 1*PCIE4/1*AGP/4xPCI/1*HDMI_SPDIF header, 6CH HD AUDIO, LAN, 2*ATA133 / 2*SATA II , 3.0Gb/s, RAID 0,1 | | |

| CARCASE/SURSE | |
|--|-----|
| CARCASA ATX 450W P4 BLACK/SILVER | 120 |
| CARCASA ATX 500W P4 BLACK/SILVER | 140 |
| CARCASA ASUS, Air Duct, 2 USB 2.0 + Audio + Mic, Fan 80mm/sleeve + buzzer, 4bay, 7 | 109 |
| CARCASA Foxconn, Air Duct w/filter, 4 USB 2.0 + Audio + Mic, Fan 80mm/CS; W/out | 126 |
| SURSA ATX 450W Delux conector 2xSATA | 71 |
| SURSA ATX 500W Delux conector SATA, 2 ventilatoare | 104 |
| SURSA ATX 600W Delux, dual 12V, 20pin+4pin, 3xS-ATA, PCI-E, Retail | 142 |
| SURSA ATX 650W Delux, dual 12V, 20pin+4pin, 3xS-ATA, PCI-E, P8, ventilator 12cm | 222 |
| SURSA ATX 380W SPIRE SP-ATX-380WTFN-PFC Jewel, 12 cm silent fan variable speed, | 113 |
| SURSA ATX 420W SPIRE SP-ATX-420WTFN-PFC Jewel 420, 12 cm fan, 21dBA, Intel ATX 2.0 | 149 |
| SURSA ATX 400W CHIEFTEC Smart, 12cm Fans, PFC, GPS-400AA-101A-RETAIL | 239 |
| SURSA ATX 650W CHIEFTEC SUPER SERIES CFT-650-14CS, 624W MAX REAL, CAI | 418 |
| SURSA ATX 750W CHIEFTEC SUPER SERIES, EPS12V, CABLE MANAGEMENT NE | 472 |
| 140MM SILENT FAN <27dB, ACTIVE PFC, EFFICIENCY >80%, SLI+CROSSFIRE READY | |
| Corsair VX450W, Quiet single-fan (1x 120mm), eficienta -85%, OVP/OCP/SCP/UVP/OPP | 364 |
| Corsair HX620W, Quiet single-fan (1x 120mm), eficienta -80% @ 50C, OVP/OCP/SCP/UV | 609 |
| Corsair TX650W, Quiet single-fan (1x 120mm), eficienta -80% @ 50C, OVP/OCP/SCP/UV | 501 |
| Corsair TX750W, Quiet single-fan (1x 120mm), eficienta -85%, OVP/OCP/SCP/UVP/OPP | 633 |

| MEMORII | |
|--|-----|
| DDR 512MB, PC3200 400MHz, KINGMAX | 99 |
| DDR 1GB, PC3200 400MHz, KINGMAX | 194 |
| DDR2 1GB, 240 pini, PC6400 800MHz KINGMAX | 104 |
| DDR2 2GB, 240 pini, PC6400 800MHz KINGMAX | 198 |
| DDR2 2GB PC6400 800MHz Non-ECC CL5 (Kit of 2x1GB) Dual Ch- ValueRam KINGSTON | 222 |
| DDR2 4GB PC6400 800MHz Non-ECC CL5 (Kit of 2x2GB) Dual Ch- ValueRam KINGSTON | 422 |
| DDR2 1GB PC8500 1066MHz KINGMAX | 106 |
| DDR2 2GB PC8500 1066MHz KINGMAX | 206 |
| DDR3 1GB, 1333MHz PC10600 FBGA Mars KINGMAX | 102 |
| DDR3 2GB, 1333MHz PC10600 FBGA Mars KINGMAX | 188 |
| SODIMM DDR400 512MB PC3200 KINGMAX | 105 |
| SODIMM DDR2/667 1GB PC5300 FBGA Mars KINGMAX | 102 |
| SODIMM DDR2/667 2GB PC5300 FBGA Mars KINGMAX | 195 |
| SODIMM DDR2/800 1GB PC5300 FBGA Mars KINGMAX | 102 |
| SODIMM DDR2/800 2GB PC5300 FBGA Mars KINGMAX | 198 |

| MEMORII FLASH | |
|--|-----|
| SECURE DIGITAL CARD 2GB KINGSTON | 30 |
| SECURE DIGITAL CARD 4GB SDHC KINGSTON | 43 |
| SECURE DIGITAL CARD 8GB SDHC KINGSTON | 77 |
| Micro-SD Card 2GB KINGSTON | 31 |
| Micro-SD Card 4GB KINGSTON | 43 |
| Micro-SD Card 8GB KINGSTON | 78 |
| PEN DRIVE 2 GB USB 2.0 KINGSTON | 30 |
| PEN DRIVE 4 GB, USB 2.0 KINGSTON | 37 |
| PEN DRIVE 8 GB, USB 2.0 KINGSTON | 67 |
| PEN DRIVE 16 GB, USB 2.0 KINGSTON | 134 |
| PEN DRIVE 32 GB, USB 2.0 KINGSTON | 279 |
| PEN DRIVE 4GB USB DataTraveler 410, 15 MB/sec read 6 MB/sec write KINGSTON | 52 |
| PEN DRIVE 8GB USB DataTraveler 410, 15 MB/sec read 6 MB/sec write KINGSTON | 92 |
| PEN DRIVE 16GB USB DataTraveler410, 15 MB/sec read 6 MB/sec write KINGSTON | 172 |
| PEN DRIVE C802 2GB, negru, conector USB retractabil A-DATA | 31 |
| PEN DRIVE C802 4GB, negru, conector USB retractabil A-DATA | 40 |
| PEN DRIVE C802 8GB, culoare neagra, conector USB retractabil A-DATA | 73 |
| PEN DRIVE 16GB MyFlash C905 UFDtoGO (download gratuit), carcasa din aluminiu, culo | 148 |
| Card Reader/Writer 52 in 1 + 1*USB2.0 port, Internal Black | 28 |
| Card Reader USB 2.0 Hi-Speed 15-in-1 CF/SM/MMC/SD/MS/MD KINGSTON | 61 |

| TV TUNER LEADTEK | |
|--|-----|
| TV2000XP Global FM Tuner TV/FM intern PAL BG/DK 10bit (Conexant CX23881) | 142 |
| DTV2000 DS Tuner TV/FM intern digital dual (2x DVB-T) PAL BG/DK/Secam/NTSC | 223 |
| DTV2000 H Plus Tuner TV/FM intern hibrid (Analog + DVB-T) PAL BG/DK 10bit (C | 246 |
| DVR3100 H Tuner TV/FM intern hibrid (Analog + DVB-T) PAL BG/DK 10bit (Conex | 337 |
| DTV DONGLE H Tuner TV extern hibrid USB 2.0 (Analog + DVB-T) PAL BG/DK Di | 261 |
| PalmTop TV Plus Tuner TV extern USB 2.0 + FM PAL BG/DK, NTSC, SECAM 10bit | 258 |
| DTV200 H Tuner TV extern hibrid USB 2.0 (Analog + DVB-T) PAL BG/DK Conexan | 287 |
| TV Pro 1920 Tuner TV extern stand alone PAL BG/DK Averlogic AL260c | 314 |
| Telecomanda StereoTV. Senzor lumina pentru ajustare automata a imaginii, Rezol | . |

| SOUND CARDS | |
|---|-----|
| GENIUS LIVE 5.1 PCI, CM8738, Retail | 50 |
| ASUS XONAR DS 7.1 Channel Audio Card with PCI Interface, SPDIF Out, Line In/ Mac in | 280 |
| ASUS XONAR-DX 7.1 Channel Audio Card with PCIe interface, Low Profile design, 116d | 416 |

| SCANNER | |
|--|-----|
| CANON LIDE 100, Flatbed Scanner format A4, optical resolution 2400x4800 dpi, Scan | 295 |
| CANON LIDE 200, Flatbed Scanner format A4, optical resolution 4800x4800 dpi, (select | 384 |
| CANON 5600F, Flatbed & Film Scanner format A4, optical resolution 4800x9600 dpi, (| 646 |

| PLACI VIDEO | |
|--|-------|
| ASUS | |
| GF8400GS, PCIE*2.0, 512MB DDR2-64bit, DVI-I; HDCP, Passive EN8400GSILP512M | 169 |
| GF210 PCIE*2.0, 512MB DDR2-64bit, HDTV, 2*DVI-I (1HDCP), Native HDMI EN210/DI/512MD2LP | 218 |
| GF9500GT, PCIE*, 1024MB DDR2-128bit, HDTV, 2*DVI-I (1HDCP), Native HDMI EN9500GTDI1GD2V2 | 311 |
| GFGT220 PCIE*2.0, 512MB DDR3-128bit, 1*DVI-I (1HDCP), Native HDMI ENGT220/DI/512MD3 | 327 |
| GFGT220 PCIE*2.0, 1024MB DDR2-128bit, 1*DVI-I (1HDCP), Native HDMI, LP bracket inside ENGT220DI1GD2(LP) | 327 |
| GFGT220 PCIE*2.0, 1024MB DDR3-128bit, 1*DVI-I (1HDCP), Native HDMI, LP bracket inside ENGT220DI1GD3(LP) | 360 |
| GFGT240, PCIE* 2.0, 512MB DDR5-128bit, DVI-I*1(HDCP support), native HDMI ENGT240/DI/512MD5 | 389 |
| GFGT240, PCIE* 2.0, 1024MB DDR3-128bit, HDTV, DVI-I (1HDCP), native HDMI ENGT240/DI/1GD3 | 415 |
| GFGTS250, PCIE 2.0, 512MB, DDR3-256bit, 2*DVI-I (1*HDCP) ENGT250DI512MD3 | 582 |
| ATI RADEON HD 4350, PCIE* 2.0, 512MB, DDR3-256bit, 2*DVI-I (1*HDCP), Native HDMI ENGT520DI1GD3 | 674 |
| GFGTX460, PCIE 2.0, 768MB, DDR5-192bit, DVI/HDMI/VGA ENGT460/2DI/768D5 | 986 |
| GF GTX470, PCIE 2.0, 1280MB, DDR5-320bit, 2*DVI-I (1*HDCP), Native HDMI ENGT470/2DI/1280M | 1,423 |
| ATI RADEON HD 4350, PCIE* 2.0, 512MB DDR2-64bit, HDTV, DVI-I, Native HDMI + LP bracket inside, Passive EAH4350SDI512M | 180 |
| ATI RADEON HD 4350, PCIE* 2.0, 1024MB DDR2-64bit, HDCP, DVI-I, Native HDMI, Passive EAH4350SDI1GD2 | 209 |
| ATI RADEON HD 4650, PCIE* 2.0, 1024MB DDR2-128bit, HDTV, DVI-I, Native HDMI, LP bracket EAH4650DI1GD2LP | 277 |
| ATI RADEON HD 4670, PCIE* 2.0, 512MB DDR3-128bit, HDTV, DVI-I, Native HDMI EAH4670DI512MD3 | 328 |
| ATI RADEON HD 4670, PCIE* 2.0, 1024MB DDR3-128bit, HDTV, DVI-I, Native HDMI EAH4670DI1GD3V2 | 374 |
| ATI RADEON HD 4850, PCIE* 2.0, 1024MB DDR3-256bit, HDTV, DVI-I*2(1HDCP), DVI to HDMI adaptor, ASUS exclusive Glacier | 530 |
| ATI RADEON HD 5450, PCIE* 2.1, 1024MB DDR3-64bit, DVI-I*1(HDCP support), native HDMI, LP bracket inside,DX11 | 295 |
| ATI RADEON HD 5570, PCIE* 2.1, 1024MB DDR3-128bit, DVI-I*1(HDCP support), native HDMI, LP bracket inside,DX11 EAH5570 | 425 |
| ATI RADEON HD 5670, PCIE* 2.1, 512MB DDR5-128bit, DVI-I*2(HDCP support), native HDMI, LP bracket inside,DX11 EAH5670/ | 467 |
| ATI RADEON HD 5670, PCIE* 2.1, 1024MB GDDR5-128bit, VGA, DVI-I*(1HDCP), native HDMI EAH5670/DI/1GD5 | 535 |
| ATI RADEON HD 5750, PCIE* 2.0, 1024MB DDR5-128bit, DVI-I*2(1HDCP), native HDMI EAH5750/2DI51GD5 | 679 |
| ATI RADEON HD 5770, PCIE* 2.1, 512MB DDR5-128bit, DVI-I*2(HDCP support), native HDMI, DX11 EAH5770/2DI/512MD5 | 672 |
| ATI RADEON HD 5850, PCIE* 2.1, 1024MB DDR5-256bit, DVI-I*2(1HDCP), native HDMI EAH5850/2DI51GD5 | 1,453 |
| GIGABYTE | |
| GeForce with CUDA 8400GS, PCI-E, 512MB, 64 bit, DDR2, DVI-I, TwinView, Scream Cooling, HDCP, CUDA enabled, low | 167 |
| GeForce with CUDA G210, PCI-E 2.0, 512MB, 64 bit, GDDR2, HDCP, HDMI(native), DL-DVI, FAN, OC, Gamer Hud Lite N2 | 203 |
| GeForce with CUDA G210, PCI-E 2.0, 1GB, 128 bit, DDR2, HDCP, HDMI(native), DL-DVI, GBT FAN N210D2-1GI | 275 |
| GeForce with CUDA GT220, PCI-E 2.0, 1GB, 128 bit, DDR2, HDCP, HDMI(native), DL-DVI, GBT FAN N220D2-1GI | 334 |
| GeForce with CUDA GT220, PCI-E 2.0, 1GB, 128 bit, DDR3, HDCP, HDMI(native), DL-DVI, FAN, OC, Gamer Hud Lite N220C | 368 |
| GeForce with CUDA GT240, PCI-E, 512MB, 128bit, GDDR5, HDCP, HDMI, DL-DVI-I, GBT FAN, CUDA enabled N240D5-512 | 374 |
| GeForce with CUDA GT240, PCI-E, 1GB, 128bit, DDR3, HDCP, HDMI, DL-DVI-I, GBT FAN, CUDA enabled | 424 |
| GeForce with CUDA GT240, PCI-E, 1GB, 128bit, GDDR5, HDCP, HDMI, 2xDL-DVI-I, GBT FAN, CUDA enabled N240OC-1GI | 456 |
| GeForce GTS250 OC, PCI-E, 1GB, 256bit, GDDR3, DL-DVI-I, HDMI, HDCP, OC, ZALMAN N250OC-1GI | 677 |
| GeForce GTX465, PCI-E, 1GB, 256bit, GDDR5, HDMI, 2xDL-DVI, HDCP N465UD-1GI | 1,150 |
| GeForce GTX470, PCI-E, 1280MB, 320bit, GDDR5, HDMI, 2xDL-DVI, HDCP, OC N470OC-13I | 1,611 |
| ATI Radeon HD 4350, PCI-E, 512MB, 64 bit, GDDR2, TV-Out, DVI-I, TwinView, FANSINK, HDCP, HDMI R435OC-512I | 167 |
| ATI Radeon HD 4550, PCI-E, 512MB, 64 bit, GDDR3, TV-Out, DVI-I, TwinView, Scream Cooling, HDCP, HDMI R455D3-512I | 208 |
| ATI Radeon HD 4650, PCI-E, 1GB, 128 bit, GDDR2, TV-Out, DVI-I, TwinView, FANSINK, HDCP R465OC-1GI | 302 |
| ATI Radeon HD 4670, PCI-E, 1GB, 128 bit, GDDR3, HDCP, HDMI, DL-DVI-I, TwinView, ZALMAN R467ZL-1GI | 356 |
| ATI Radeon HD 5570, PCI-E 2.0, 1GB, 128 bit, DDR3, HDCP, HDMI(native), DL-DVI, DirectX® 11, ATI Eyefinity R557OC-1GI | 402 |
| ATI Radeon HD 5670, PCI-E 2.0, 1GB, 128 bit, GDDR5, HDCP, HDMI(native), DL-DVI, DirectX® 11, ATI Eyefinity R567OC-1GI | 474 |
| ATI Radeon HD 4850, PCI-E, 512MB, 256 bit, GDDR3, DVI-I, TwinView, Zalman, HDCP R485ZL-512H | 474 |
| ATI Radeon HD 5450, PCI-E 2.0, 1GB, 64bit, DDR3, HDCP, HDMI(native), DL-DVI, DirectX® 11, ATI Eyefinity R545SC-1GI | 289 |
| ATI Radeon HD 5750, PCI-E 2.0, 1GB, 128 bit, GDDR5, HDCP, HDMI(native), 2xDL-DVI, Display Port, DirectX® 11, ATI Eyefini | 645 |
| ATI Radeon HD 5770, PCI-E 2.0, 1GB, 128 bit, GDDR5, HDCP, HDMI(native), 2xDL-DVI, Display Port, DirectX® 11, ATI Eyefinity | 767 |
| SAPPHIRE | |
| ATI Radeon HD 3450 AGP 8x 512MB DDR2 64bit, 600/800MHz, DVI/HDMI, Fan cooler, HDTV, Lite Retail | 226 |
| ATI Radeon HD 3650 AGP 8x 512MB DDR2 128bit, 600/800MHz, Single Slot Fan Cooler, DVI/TVO, Lite Retail | 261 |
| ATI Radeon HD 4650 AGP 8x 1024MB DDR2 128bit, 600/800MHz, Dual DVI/TVO, Single Slot Fan Cooler, HDTV, HDMI ada | 406 |
| ATI Radeon HD4350 PCI-EX2.0 256MB DDR2 64bit, 600/600MHz, DVI/VGA, Heatsink, HDTV, HDMI on board, CrossfireX, L | 142 |
| ATI Radeon HD4650 PCI-EX2.0 512MB DDR2 64bit, 600/1000MHz, DVI/TVO, Single Slot Fan Cooler, HDTV, HDMI, Crossfire | 194 |
| ATI Radeon HD4670 PCI-EX2.0 1024MB GDDR3 128bit, 750/1600MHz, DVI/VGA, Dual Slot Fan Cooler, HDMI, CrossfireX, L | 370 |
| ATI Radeon HD5570 PCI-EX2.0 1024MB GDDR3 128bit, 650/1800MHz, HDMI/DVI/VGA, Single Slot Fan Cooler, HDTV, Cros | 408 |
| ATI Radeon HD5750 PCI-EX2.1 1024MB DDR5 128bit, 700/2300 Mhz, DUAL DVI-I / HDMI/Display Port , Dual Fan Cooler | 672 |
| ATI Radeon HD5750 Vapor-X PCI-EX2.1 1024MB GDDR5 128bit, 710/2130 Mhz, DUAL DVI-I / HDMI/Display Port , Dual Fa | 735 |
| ATI RADEON HD5830 PCI-EX2.1 1024MB GDDR5 256bit, 800/2000MHz, DUAL DVI-I / HDMI / Display Port, Dual Slot Fan Co | 997 |
| LEADTEK | |
| WinFast PX8400 GS 512 8400 GS 567 MHz 512MB DDR2 667MHz, 64 bit TV-Out, Dual-Link DVI, VGA Full DirectX 10 | 164 |
| WinFast 210 512 DDR2 LP 210 589MHz 512MB DDR2 800MHz, 64bit VGA, Dual-Link DVI, HDMI DirectX 10, PureVid | 213 |
| WinFast 210 512 DDR3 LP 210 589MHz 512MB DDR3 1580MHz, 64bit VGA, Dual-Link DVI, HDMI DirectX 10, PureVid | 241 |
| WinFast PX9400 GT 512 LP 9400 GT 550 MHz 512MB GDDR2 800MHz 128bit VGA, Dual-Link DVI, HDMI DirectX 10 | 208 |
| WinFast PX9500 GT 512 LP 9500 GT 550 MHz 512MB GDDR2 800MHz, 128bit VGA, Dual-Link DVI, HDMI DirectX 10 | 238 |
| WinFast PX9500 GT 512 DDR3 9500 GT 550 MHz 512MB GDDR3 1600MHz, 128bit VGA, Dual-Link DVI, HDMI Direct | 290 |
| WinFast PX9500 GT 1024 LP 9500 GT 550 MHz 1024MB DDR2 800MHz, 128bit VGA, Dual-Link DVI, HDMI DirectX 10 | 293 |
| WinFast GT220 1024 DDR2 LP GT220 625 MHz 1024MB DDR2 1000MHz, 128bit VGA, Dual-Link DVI, HDMI DirectX 10 | 331 |
| WinFast GT220 1024 DDR3 LP GT220 625 MHz 1024MB DDR3 1580MHz, 128bit VGA, Dual-Link DVI, HDMI HDTV, D | 372 |
| WinFast GT240 512 DDR3 GT240 550 MHz 512MB DDR3 2000MHz, 128bit VGA, Dual-Link DVI, HDMI DirectX 10.1, F | 422 |
| WinFast GT240 512 DDR5 GT240 550 MHz 512MB DDR5 3600MHz, 128bit VGA, Dual-Link DVI, HDMI DirectX 10.1, F | 438 |
| WinFast GT240 1024 DDR3 GT240 550 MHz 1024MB DDR3 1580MHz, 128bit VGA, Dual-Link DVI, HDMI DirectX 10.1 | 482 |
| WinFast PX9800 GT 512 9800 GT 550 MHz 512MB DDR3 1400MHz, 256bit Dual-Link DVI, HDMI, D-Sub DirectX 10, N | 457 |
| WinFast GT250 512 LP GTS250 675 MHz 512MB DDR3 2000MHz, 256bit Dual Dual-Link DVI DirectX 10, NVIDIA P | 553 |
| WinFast GTS250 1024 LP GTS250 675 MHz 1024MB DDR3 1800MHz, 256bit Dual Dual-Link DVI DirectX 10, NVIDIA | 616 |
| WinFast GTX460 768 GTX 460 (FERMI) 675 MHz (CUDA core 336) 768MB DDR5 3600MHz, 192bit 2x Dual-Link DVI, n | 1,002 |

| RETELISTICA | |
|--|-----|
| Placa retea PCI-UTP 10/100 REALTEK | 21 |
| Placa retea Wireless USB DWL-G122 D-LINK | 82 |
| Placa retea Wireless WL-167G_V2 ASUS | 70 |
| Switch 5 porturi Fast Ethernet 10/100 EDIMAX | 48 |
| Switch 8 porturi Fast Ethernet 10/100 RPC/EDIMAX | 63 |
| Router RPC-IP2105 1xWan/4P 10/100 Mbps switch MDI/MDI-X, hardware Firewall | 84 |
| Router Wireless WL-520GC ASUS 4P 802.11g BroadRange 125*High Speed mode | 167 |
| Router Wireless DIR-300 4 porturi 10/100 Wireless G | 127 |
| Router Wireless N D-link DIR-615 | 198 |
| CABLU UTP CAT 5E / M | 1 |
| MUFE UTP RJ45 | 1 |

| SOFTWARE | |
|---|-----|
| SISTEME DE OPERARE | |
| Microsoft Windows Vista Home Basic 32 bit SP1 English/Romanian | 404 |
| Microsoft Windows Vista Business 32/64 bit SP1 English/Romanian | 648 |
| Microsoft Windows 7 Home Premium 32/64 bit English/Romanian | 509 |
| Microsoft Windows 7 Pro 32/64 bit English/Romanian | 663 |
| Microsoft Windows 7 Ultimate 32/64 bit English/Romanian | 912 |
| Microsoft Windows XP Professional English GKG - pentru legalizare | 799 |
| Microsoft Windows Vista Business English GKG - pentru legalizare | 799 |
| Microsoft Windows 7 Professional 32/64bit English GKG - pentru legalizare | 821 |

| APLICATII | |
|---|-------|
| Office Home and Business 2010 English PC Attach Key PKC Microcase | 969 |
| Office Small Business Ed 2007 Win32 English 1pk DSP OEM w/OfcProTri(MLK) (Word 2007, Excel 2007, PowerPoint 2007, Outlook 2007 with Business Contact Manager, Publisher 2007) | 1,142 |
| Office Pro 2007 Win32 English 1pk DSP OEM (MLK) (Word 2007, Excel 2007, Outlook 2007 with Business Contact Manager, PowerPoint 2007, Publisher 2007, Access 2007) | 1,424 |
| FPP Office Home and Business 2010 32-bit/x64 English Intl DVD Retail | 1,415 |

| ANTIVIRUSI | |
|---|-----|
| BitDefender Antivirus v2010 OEM cu CD kit 1 user 1 an | 45 |
| BitDefender Antivirus v2010 Retail 3 licente 1 an Antivirus & Antispyware, Anti-phishing | 120 |
| BitDefender Internet Security v2010 Retail 3 licente 1 an Antivirus & Antispyware, Anti-phishing | 174 |
| BitDefender Total Security v2010 Retail 3 licente 1 an Antivirus & Antispyware, Anti-phishing, Protectia retelei personale, Mod pentru jocuri, Mod pentru laptop, Antispyware | 246 |
| Kaspersky Anti-Virus 2010 - 1 user - 1 year - BOX - limba romana PROMO | 101 |
| Kaspersky Anti-Virus 2010 - 3 users - 1 year - BOX | 325 |
| Kaspersky Internet Security 2010 - 1 user - 1 year - BOX - romana PROMO | 152 |
| Kaspersky Internet Security 2010 - 3 users - 1 year - BOX | 433 |

| SURSE DE PROTECTIE | |
|--|-----|
| V-MARK UPS-500VP, 500VA, 8 min back-up (half load), LCD Display | 210 |
| V-MARK UPS-650VP, 650VA, 8 min back-up (half load), LCD Display | 219 |
| V-MARK UPS-800VP, 800VA, 8 min back-up (half load), LCD Display | 305 |
| V-MARK UPS-1000VP, 1000VA, 8 min back-up (half load), LCD Display, Power Manager | 373 |
| V-MARK UPS-1200VP, 1200VA, 8 min back-up (half load), LCD Display, Power Manager | 387 |
| V-MARK UPS-2000SD, 2000VA, 8 min back-up (half load), LCD Display, Power Manager | 801 |
| APC Back-UPS ES, 400VA/240W BE400-GR | 353 |
| APC Back-UPS ES, 550VA/330W Power-Saving BE550G-GR | 407 |
| APC Back-UPS CS, 350VA/210W, off-line BK350EI | 386 |
| APC Back-UPS CS, 500VA/300W, off-line BK500EI | 473 |
| AVR600M APOLLO Automatic Voltage Regulator 600VA relay type | 63 |

| UNITATI OPTICE | |
|---|-------|
| DVDRW ASUS DRW-22B2S-bulk-B 22xDVDRW Black Bulk | 114 |
| DVDRW ASUS DRW-22B2L/B+W 22xDVDRW + Lightscribe Dual Panel Retail | 127 |
| DVDRW ASUS DRW-24B1ST-B 24xDVDRW Black Retail SATA | 106 |
| DVDRW ASUS DRW-24B1LT/B+W 24xDVDRW SATA + Lightscribe Dual Panel(B+W) Retail | 125 |
| DVDRW ASUS SDRW-08D1S-U/B 8xDVDRW - External Slim, Black Retail | 249 |
| DVDRW LG GH22NS40 22xDVDRW SATA Bare Bulk Black | 91 |
| DVDRW LG GH22LP20B 20xDVDRW + Lightscribe Bulk Black | 116 |
| DVDRW LG GE20LU11 20xDVDRW + Lightscribe Extern USB2.0 Retail | 215 |
| DVDRW LG GP08LU11 8xDVDRW + Lightscribe Extern USB2.0, Slim | 239 |
| BLUERAY LG BH10LS30R BluRay Writer SATA Retail Black (8x BD-R Read, 3x HD DVD Read) | 774 |
| BLUERAY LG BE08LU20 BluRay Writer Extern USB2.0 Retail | 1,074 |
| DVDRW Samsung SH-S223C/BEBE 22xDVDRW SATA Bulk Black | 80 |
| DVDRW Samsung SH-S223L/RMS5 22xDVDRW SATA + Lightscribe Retail (includes beige) | 110 |
| DVDRW Samsung SN-S083C/BEBE 8xDVDRW SATA Bulk Black Slim for notebooks | 163 |
| DVDRW Samsung SE-S084C/USBS 8xDVDRW Retail Slim Black - Extern USB2.0 | 233 |

| CAMERE WEB | |
|--|-----|
| Genius i-Slim 300x, 3200 x 2400 (8MP), 640 x 480 Video, 30fps, Clipping for Desktop | 53 |
| Genius i-Look 300, 300K, 3360 x 2520(8MP) Image, 1.3MP Video, Clipping for Desktop | 48 |
| Genius eFace 1300, 1.3MP, 3360 x 2520(8MP) Image, 640x480 Video, Microfon, rotatie | 90 |
| Genius eFace 2025, 2MP, 3360 x 2520(8MP) Image, HD video in 1280 x 720, 30fps, 1.3MP Video | 131 |
| A4TECH PK-5, 350K USB PC camera, adjustable height, 360 degree rotation, microp | 68 |
| A4TECH PK-336E BLACK Senzor CMOS 640x480 350K Pixeli, pana la 5M Pixeli, 2560x1920 | 51 |
| CANYON CNR-WCAM413G (1.3Mpixel CMOS, USB) & Game "Star Fish", Black/Blue | 68 |
| CANYON CNR-WCAM613G (1.3Mpixel CMOS, USB 2.0) & Game "Star Fish", Black/Orange | 68 |
| CANYON CNR-WCAM820 2.0MP Webcam black/silver + StarFish Game | 105 |

| MONITORE | |
|--|-------|
| ASUS | |
| 19" ASUS VW193DR TFT Wide Screen 1440x900 - 5ms Contrast: 1000:1 (ASCR 50000:1) 0.285mm 300cd/m2, Inputs: D-Sub, VGA, DVI, USB | 540 |
| 19" ASUS VH198D LED Wide Screen 1440x900 - 5ms Contrast: 1000:1 (ASCR 10000000:1) 0.285mm 250cd/m2, 1W (RM), 16:9 | 590 |
| 22" ASUS VH222D TFT Wide Screen 1920x1080 - 5ms Contrast: 1000:1 (ASCR 20000:1) 0.248mm 300cd/m2, Full HD, In | 671 |
| 22" ASUS VW225D TFT Wide Screen 1680x1050 - 5ms Contrast: 1000:1 (ASCR 8000:1) 0.282mm 300cd/m2, Inputs: 1*DP, 1*VGA, 1*DVI | 689 |
| 22" ASUS MS227N TFT Wide Screen 1650x1050 - 2ms(GTG) Contrast: 1000:1 (ASCR 50000:1) 0.282mm 250cd/m2, Inputs: D-Sub, VGA, DVI | 870 |
| 24" ASUS VH242H TFT Wide Screen 1920x1080 - 5ms Contrast: 1000:1 (ASCR 20000:1), 0.272mm 300cd/m2, Full HD, 2 | 981 |
| 24" ASUS VW246H TFT Wide Screen 1920x1080 - 2ms(GTG) Contrast:1000:1 (ASCR 20000:1), 0.277mm 300cd/m2, Full HD, 1 | 1,092 |
| LG | |
| 19" LG W19435S-PF, Wide, 5 ms, 1366x768, 250 cd/m2, 30000:1, 170/160, VESA 75x75, Flatron fEngine, black glossy | 560 |
| 19" LG TFT W19345-BN, Wide, 5 ms, 1440x900, 300 cd/m2, 1000:1, 160/160, TCO-03, black | 583 |
| 19" LG TFT L1942SE-SF, 5 ms, 1280x1024, 250 cd/m2, 170/170, 8000:1, Flatron F-Engine, TCO-03, silver | 700 |
| 20" LG W2043SE-SF, Wide 1600x900, 5 ms, 300 cd/m2, 30000:1 DFC, Flatron f Engine, TCO-03, negru glossy | 624 |
| 22" LG E2240S-PN LED - 16:9 1920x1080 - 5 ms, 250 cd/m2, 5.000.000:1 (DFC), 176/170, semnal intrare: FULL HD D-Sub, VGA, DVI | 817 |
| 22" LG TFT W2253TQ-PF, Wide 1920x1080, 2 ms, 300 cd/m2, 50000:1, DVI, Flatron f Engine, Photo effect, glossy black | 799 |
| 22" LG W2286L-PF, WIDE 1680x1050, Slim WHITE LED(2cm), 2 ms (GTG), 250 cd/m2, 2000000:1, Flatron F-Engine, D-Sub, VGA, DVI | 963 |
| 23.6" LG W2443T-PF, Wide 1920x1080, 5 ms, 300 cd/m2, 30000:1, DVI, Flatron f Engine, TCO-03, Glossy Black | 934 |
| 24", LG W2486L, WIDE 1920x1080, Slim WHITE LED(2cm), 2 ms (GTG), 250 cd/m2, 2000000:1, Flatron F-Engine, D-Sub/VGA, DVI | 1,342 |

| SAMSUNG | |
|--|-------|
| 19" SAMSUNG TFT B1930N wide, 1360x768, 5ms, 50.000:1, 250cd/mp, 170°/160°, D-sub, High Glossy Black, Tilt | 636 |
| 19" SAMSUNG TFT 923NW-N, 1440x900, 5ms, 50.000:1, 300cd/mp, 170°/160°, VGA, D-sub, VESA, Black | 569 |
| 20" SAMSUNG TFT 2043SN Wide, 1600x900, 5 ms, 1000:1 (DCR 15.000:1), 250 cd/mp, 170/160, TCO 03, Black | 771 |
| 20" SAMSUNG TFT B2030N wide, 1600x900, 5ms, 50.000:1, 250cd/mp, 170°/160°, High Glossy Black | 765 |
| 20" SAMSUNG TFT P2050 wide, 1600x900, 5ms, 1000:1 (DCR 50.000:1), 300cd/mp, 170°/160°, D-sub/DVI, Rose/Black | 852 |
| 22" SAMSUNG TFT 2243SN wide, 1920x1080, 5 ms, 1000:1 (DCR 15000:1), 300 cd/mp, 170/160, TCO 99, Black | 870 |
| 22" SAMSUNG TFT P2250N wide, 1920x1080, 5ms, DCR 50.000:1, 300cd/mp, 170°/160°, D-sub, Rose/Black | 905 |
| 23" SAMSUNG TFT P2370 Wide, 1920x1080 2ms,DVI, 1000:1 DCR 50.000:1, 300cd/mp, 170/160 D-sub/DVI, Dark grey | 1,068 |

| BENQ | |
|--|-------|
| 19" BENQ TFT G920WL LED 1440x900 - 5ms - 5.000.000:1 - 250cd/mp - D-Sub/DVI-D - TCO03 - 17W power consumption | 566 |
| 20" BENQ TFT G2020HD 1600x900 - 5ms - 40.000:1 - 250cd/mp - D-Sub/DVI-D - Senseye+Photo - VESA - Glossy Black - Tilt | 596 |
| 22" BENQ TFT G2220HD 1920x1080 - 5ms - 40.000:1 - 300cd/mp - D-Sub/DVI-D - Senseye+Photo - VESA - Black - TCO04 | 765 |
| 24" BENQ TFT V2400ECO LED - 1920x1080 - 5ms - 5.000.000:1 - 250cd/mp - D-Sub/HDMI 1.3/Headphone - Senseye+Photo | 1,098 |

| PHILIPS | |
|---|-------|
| 19" PHILIPS TFT190C15B/00 wide, 1440x900, 5 ms, 1000:1(SCR 12000:1), 300 cd/mp, 176/160, black, VGA, DVI, USB | 584 |
| 19" PHILIPS TFT 19S15B/00, 1280x1024, 5 ms, 800:1(SCR 25000:1), 250 cd/mp, 176°/170°, silver, VGA, DVI-D, Black | 689 |
| 22" PHILIPS TFT 220E15B/00 wide, 1680x1050, 5 ms, 1000:1(SCR 12000:1), 300 cd/mp, 160/160, black, VGA | 692 |
| 22" PHILIPS TFT 225B1CS/00 wide, 1680x1050, 5 ms, 1000:1(SCR 12000:1), 300 cd/mp, 176/170, silver, VGA, DVI-D, Po | 835 |
| 23" PHILIPS TFT 231E15B/00 Wide, 1920x1080p, 5 ms, 1000:1(SCR 12000:1), 300cd/mp, 176°/170°, VGA, DVI, Glossy Bl | 806 |
| 24" PHILIPS TFT 240B9C5/00 wide, WUXGA, 1920x1200, 5 ms, 1000:1, 250 cd/mp, 160/160, Black, boxe, VGA, DVI-D | 1,570 |

| TASTATURI | |
|---|----|
| A4TECH KBS-720SB tastatura slim 108but,taste ergonomice A-Shape,PS2,Silver/Black | 26 |
| RPC-KMV-026PB Multimedia Keyboard - 19 Multimedia Keys - Black -Super design - PS/2 | 35 |
| GENIUS SlimStar 320 Black, 16 hot-key, USB | 58 |
| GENIUS LuxMate 300, slim, 9 hot keys, PS2 | 45 |

| MOUSE | |
|---|----|
| A4Tech OP-620 Mouse optic, 2but + 1wheel; rezolutie 800dpi; Conectare: PS2 | 19 |
| CANYON CNR-MSL4 (Optical 1000dpi, 4btn, USB/PS/2, Black, G-Laser Technology) Retail, 1-pk | 41 |
| CANYON CNR-MSL5A (Optical 1000dpi, 7btn, USB, Black) Retail (Blister), 1-pk | 74 |
| Genius Netscroll 120 Black, 800DPI, PS2 | 19 |
| Genius Xscroll Black, 800DPI, 3 buttons, PS2 | 21 |
| Genius Traveler 305 Silver, Mini, Laser, 1600DPI, USB | 40 |

| SISTEME DE NAVIGATIE | |
|--|-------|
| Moov500R0 Samsung2443 400MHz CPU Microsoft Windows® CE 5.0, Built in GPS module, SiRFInstantFixII, 64MB + 512MB, 4.7" TFT, Touch Panel, SD/MMC, USB 2.0, NavPix, Romania Map 2008 | 455 |
| MoovM400u 4.3" TFT, Samsung 2443 400MHz CPU Microsoft Windows® CE 5.0, Built in GPS module, 20-channel SiRFStarIII chipset, 64MB + 2GB, Brightness 320nits, Touch Panel, SD, BT data, USB 2.0, Europe | 712 |
| Spirit505 4.7" TFT, Samsung 2450 400MHz, WinCE 5.0, SiRF GPS III (20 channels) 3TW, 128MB+2GB, TMC, Navpix, Full Europe | 847 |
| Spirit555 4.7" TFT, Samsung 2450 400MHz, WinCE 5.0, SiRF GPS III (20 channels) 3TW, 128MB+2GB, BTHF, BT DUN, Navpix, Full Europe | 899 |
| Spirit5760 7" TFT, Samsung 2450 400MHz CPU Microsoft Windows® CE 5.0, Built in GPS module, 20-channel SiRFStarIII chipset with InstantFixII, 64MB + 2GB, 800x480, Touch Panel, Micro SD, AV In (Portable HDD/DVD/Digital TV) | 1,378 |

| DIGITAL VIDEO CAMERA | |
|---|-------|
| SONY SX30 Blue, MS - 4GB + 4GB/Bonus - CCD senzor - 800kP - 60x optical zoom - 2.7" TFT TACTIL hibrid LCD - Super SteadyShot - Dolby Digital AC-3 2ch cu microfon incorporat - USB 2.0 Hi-Speed | 953 |
| SONY CX116E Black, AVCHD MS - 8GB - CMOS senzor - 1.6MP - 25x optical zoom - 2.7" TFT TACTIL Clear Photo LCD SteadyShot - D-Range Optimiser - Dolby Digital AC-3 2ch cu microfon incorporat - USB2.0 Hi-Speed - iesire HDMI | 2,222 |
| SONY SR58E Silver, HDD - 80GB - CCD senzor - 800kP - 60x optical zoom - 2.7" TFT TACTIL Clear Photo LCD - SteadyShot - Dolby Digital AC-3 2ch cu microfon incorporat - USB2.0 Hi-Speed | 1,595 |
| JVC GZ-M955 Everio S 1/6" CCD-800k pixeli SD/SDHC dublu slot MPEG-2 PS, Dolby Digital (2ch), JPEG inregistrare | 779 |
| JVC GZ-MS215B Everio S 1/6" CCD-800k pixeli SD/SDHC dublu slot MPEG-2 PS, Dolby Digital (2ch), JPEG inregistrare | 935 |
| JVC GZ-HM200N Everio HD (Full HD) 1/4.1" CMOS-3.05Mpx SD/SDHC dublu slot cu inregistrare continua MPEG-4 AVC | 1,663 |

| CAMERE FOTO | |
|--|-------|
| BENQ | |
| C1250 12MP - CCD sensor - 3x optical zoom - 2.7" LCD - card support SD (4GB)/SDHC (32GB)-15MB built in memory-2xAA battery - USB - Romanian OSD - Black | 299 |
| E1230 12MP - CCD sensor - 3x optical zoom - 3" LCD - card support SD (4GB)/SDHC (32GB) - 21MB built in memory - Li-Ion battery - Romanian OSD - Silver | 416 |
| W1220 12MP - CCD sensor - 5x optical zoom - 2.7" LCD - card support SD (4GB)/SDHC (32GB) - 20B built in memory - Li-Ion battery - Romanian OSD - Black | 568 |
| SONY | |
| S2000 Black, 10.1MP - CCD sensor - 3x optical zoom - 2.5" TFT hibrid LCD - ISO3200 - memorie interna 6 MB - compatibil Memory Stick Duo™ / PRO Duo™ / PRO-H | 355 |
| W350 Black, 14.1MP - CCD sensor - 4x optical zoom - 2.7" TFT hibrid LCD - SteadyShot | 756 |
| DSC-HX1 Black, 9.1MP - CMOS EXMOR - 20x optical zoom - 3.0" TFT hibrid LCD - SteadyShot - HD Output - ISO 3200 - Smile Shutter - memorie interna 11 MB - comp | 1,829 |
| CANON | |
| PowerShot A490 10.0 MP and 3.3 optical zoom, Meniu in limba romana, DIGIC III, S | 475 |
| PowerShot A3100 IS Silver 12.1 MP and 4 optical zoom, Stabilizator optic de imagine | 711 |
| Digital IXUS 100 IS silver 12.1 MP and 3x optical zoom, HD Movies (1280x720, 30fps) | 936 |
| EOS 1000D + EF 18-55 DC EOS; obiectiv Canon EF 18-55 DC+1000D Body 10.1 Mega | 2,249 |
| sensor, Built-in/Fixed with Self Cleaning Sensor Unit, 2.5" LCD with Live View mode, carcasa Stainless Steel/Plastic; 7-point AF , DIGIC III, Shutter Speed 30-1/4000 sec (1 | |
| NIKON | |
| COOLPIX L21 (brown) 8.0 MP 3.6x 4x 6.35 cm TFT, 230.000 pixeli electronic | 350 |
| ISO 80-1600 2xAa Filmare 640x480@30fps Slot SD/SDHC Exped maro lungime x inaltime x grosime 92x61.1x28.3mm 183g 2 ani VMA581E6 | |
| COOLPIX L22 (black) 12.0 MP 3.6x 4x 7.5cm TFT, 230.000 pixeli electronic | 450 |
| ISO 80-1600 2 baterii AA alcaline(LR6/L40) - furnizate; 2 baterii AA litiu (FR6/L19) sau 2 | |
| COOLPIX S3000 (black) 12.0 MP 4x cu unghi larg 4x 6.7 cm TFT VR | 550 |
| (Stabilizator de imagine electronic si in senzor) ISO 80-3200 EN-EL10 Filmare 640x480@30fps Slot SD/SDHC Exped negru lungime x inaltime x grosime 94.3x55.9x19mm 116g 2 ani VMA541E1 | |
| COOLPIX S1000pj (black) 12.1 MP 5x cu unghi larg 4x 6.85 cm TFT, 230.000 p | 1,000 |
| VR (Stabilizator de imagine optic si electronic) ISO 80-6400 acumulator reincarcabil Li-ion EN-EL12 Filmare 640x480@30fps Slot SD/SDHC Exped proiectare 26cm-2m negru lungime x inaltime x grosime 99.5x62.5x23mm 155g | |
| D3000 kit 18-55 VR 10.2 MP 3D Color Matrix Metering II 11 puncte AF ISO 100- | 1,800 |
| (extins 3200) 1/4000s - 30s + Bulb Mod burst - 3fps Blit i-TTL, sincronizare ma | |
| 1/200s LCD 3 inch SD, suport SDHC Li-Ion EN-EL9a 485g Nikkor 18-55mm f/3.5-5.6G AF-S DX VR 2 ani VBA250K001 | |

| HP INKJET | |
|---|-------|
| DJ D1660 Printer; A4,max 20ppm black,16ppm c,USB2.0,max 4800x1200dpi,cartridge no. 300; optional no. 300XL | 141 |
| DJ D2660 Printer;A4,max 28ppm black,21ppm c,max 4800x1200dpi, USB2.0, cartridge no. 300,optional no. 300XL | 183 |
| Officejet 6000 Printer; A4, max 32ppm black, 31ppm color, 32MB, HP PCL3 GUI, 250 sheet tray, 4800x1200dpi max, USB 2.0, Ethernet, max 7.000 pag duty cycle, cartridge HP 920; optional cartridge HP 920XL | 447 |
| Officejet 7000 Wide Format; A3+, max 33 ppm black A4, 32 ppm color A4, max. 4800dpi, 32 MB, HP PCL 3 GUI, USB, Ethernet, duty cycle max 7000 pag, cartridge HP 920; optional cartridge HP 920XL | 1,130 |
| HP MULTIFUNCTIONALE | |
| Deskjet F2480 All-in-One; Printer, Scanner, Copier, A4, print: max 20ppm a/n, 16ppm color, min. 28sec/ foto 10x15cm, ma | 274 |
| Photosmart C4680 All-in-One; Printer, Scanner, Copier, A4, print: max 29ppm a/n, 23ppm color, scanner: flatbed, max 1200x2400dpi hardware; copy: max 5.5cpm a/n, 6.5cpm color; cititor de carduri, LCD color; USB 2.0, cartridge HP 300, ma | 350 |
| Officejet J4580 All-in-One;Printer,Fax,Scanner,Copier,A4, print,max 28ppm a/n,22ppm color,scanner.flatbed, max 1200dpi optic, 48 bit adincime de culoare,fax: color, 33,6kbps, 3sec/pag, USB 2.0, cartridge no. 901, optional negru no. 901XL | 409 |
| Photosmart B109a; Printer, Scanner, Copier, A4, print: 30ppm a/n, 28ppm, scanner: flatbed, max 1200x2400dpi hardware; copy: 9cpm a/n, 10.5cpm c,cititor de carduri, LCD color 3.68cm TouchFrame; USB 2.0; cartridge HP 364, opt.364XL | 361 |
| Officejet 6500 All-in-One; Printer, Fax, Scanner, Copier, A4, print: max 32ppm a/n, 31ppm color,4800x1200dpi, 32MB, scanner: max 2400x4800dpi optic, copy: max 32cpm a/n, 31cpm color, USB 2.0, Ethernet, slot carduri de memorie, cartridge no. 920, max 7.000pag/luna; optional cartridge no. 920XL | 519 |
| HP LASER MONOCROM + COLOR | |
| LaserJet Pro P1102; A4, 18ppm,600x600dpi, 2MB RAM,, 150 coli, USB, toner 700 pag, max 5.000pag/luna, toner CE285A | 485 |
| LaserJet Pro P1102w; A4, max 18ppm, max 600x600dpi (HP FastRes 1200), 8MB RAM, fpo 8.5 sec, host-based printing driver, 150 coli, USB, wireless, toner 700 pag, max 5.000pag/luna, recomandat 250-1.500 pag/luna; optional toner CE285A | 576 |
| LaserJet Pro P1566; A4, 22ppm, 600x600dpi, 8MB RAM, 250+10 coli, USB, toner 1000 pag, max 8.000pag/luna, CE278A | 712 |
| Color LaserJet C1215; A4, max 12ppm a/n, 8ppm color, 16MB, max 600x600dpi ImageRet2400, fpo 24 sec a/n, 30 sec color | 909 |
| HP MULTIFUNCTIONAL LASER MONOCROM | |
| LaserJet M1132 MFP; A4, max 18ppm, max 600x600dpi, 8MB, fpo 8.5 sec, tavi 10+150 coli, scan: flatbed, max 1200dpi 24 bit adincime de culoare,USB 2.0,toner 700 pag, max 8.000pag/luna, recomandat 250-2.000 pag/luna, toner CE285A | 661 |
| LaserJet M1319F MFP; A4, max 18ppm, max 1200x1200dpi, 32MB, tava 250 coli, LCD 2 linii, scanner: fax 33.6kbps, receptor, ADF 30 coli, USB2.0, toner 1000 pag, max 8.000pag/luna, optional Q2612A | 1,343 |
| CANON BUBBLE JET | |
| PiXMA iP2700, A4, imprimanta inkjet color A4, 7ipm A/N, 4.8ipmcolor, 4800x1200dpi, PG-510, CL-511 (Optional - PG-512, CL-513) - interfata USB, Imprimare fara margini albe | 188 |
| PiXMA iP3600, A4, 26ppm/17 ppm color, 9600x2400dpi, PGI-520BK, CLI-521BK, CLI-521C, CLI-521M, CLI-521Y - iRear Tray: Imprimare fara margini albe , Windows Vista (32bit, 64bit) / Windows XP SP2 / Windows 2000 Professional SP4, Mac OS X v.10 | 341 |
| PiXMA iP4700, Imprimanta inkjet color A4, 10x15 cm borderless photo in app. 20 sec, 9600*2400 dpi, 1 pl, 5 single inks, auto duplex, 2-way paper feeding, DVD/CD printing, PictBridge, CromLife100+ | 424 |
| PiXMA iX4000, A3+, 18ppm A/N, 14ppm colour (A4), 4800 x 1200 dpi , Single Ink technology - 4 separate ink tanks (PGI-5BK, CLI-8C, CLI-8M, CLI-8Y), Media Input : Sheet feeder: 150 sheets, Media weight : Sheet feeder: 64 to 105 g/m ² and | 1,228 |
| CANON MULTIFUNCTIONAL BUBBLE JET | |
| PiXMA MP270, A4, 8.4ipm mono, 4.8ipm color, rezolutie 4800 x 1200 dpi, Print/Scan/Copy & Camera direct printing, USB 2.0 Hi-Speed, Direct Printing, greutate 5.6 kg, consumabile: PG-510, CL-511 | 232 |
| PiXMA MX320, A4, 4-in-1: Printer, Scanner, Copier and Fax, 30-sheet ADF, 4800x1200dpi*,1200x2400 scanner & Scan to USB, fax standalone 33.6kbps, copiator, consumabile: PG-510, CL-511 (Optional - PG-512, CL-513); Full dot LCD display; interfata | 339 |
| CANON LASER | |
| LBP3010 A4, 14 ppm, 2400 x 600 dpi equivalent, USB 2.0, 2MB RAM, Cartridge Cartridge 712 (1,500 pages), Optional Network | 421 |
| LBP3310, A4, 26ppm, rezolutie 600 x 600dpi, duplex printing, automatic Image Refinement, 2400 x 600 dpi equivalent, USB 2.0, consumabil:CRG-715 (3000 pag, optional CRG-715H- 7000 pag) | 1,002 |
| LBP3370, A4, 26 ppm, UFRII (Ultra Fast Rendering) & PCL 5e and PCL 6 , built-in network Interface with Remote User Interfa | 1,613 |
| LBP5050, A4 8 colour/12 ppm mono laser printer, 600 x 600 dpi , Cartridge 716 Black, 716 C / M / Y | 867 |
| CANON MULTIFUNCTIONAL LASER | |
| i-SENSYS MF4010, Multifunctional laser mono A4, Print, Scan (Flatbed), 20 ppm, 600 x 600 dpi; : 32MB; Cartridges : All-in-One Cartridge FX-10 - 2000 pages (Based on 5% coverage) | 838 |
| i-SENSYS MF4320D, Multif. laser mono A4, Print/Copy/Duplex/Colour Scanner, 22 ppm, CARTRIDGE FX10 | 933 |
| i-SENSYS MF4340D, Multif. laser mono A4, Print/Copy/Fax/Duplex/Colour Scanner, 22 ppm, CARTRIDGE FX10 | 1,103 |
| SAMSUNG IMPRIMANTE LASER MONOCROM/COLOR | |
| ML-1660, A4, max 16 ppm, max 1200x600 dpi, fpo 8.5 sec, 8 MB RAM, 150 coli, USB2.0, toner 700 pag, max 5.000pag/luna; 48 | 385 |
| ML-1915, A4, max 18ppm, max 1200x600 dpi, fpo 10 sec, 8MB RAM, SPL, 250 coli, USB2.0, toner 700 pag, max 10.000 pag/lt | 403 |
| CLP-310 16/4 ppm, Color Laser, 2400x600dpi, 32MB, USB 2.0, gri | 721 |
| SAMSUNG MULTIFUNCTIONALE LASER | |
| SCX-4300; A4, max 18ppm, max 600x600dpi, 8MB, fpo 11 sec, SPL, 250 coli, LCD 2 linii, copy: max 18cpm, max 600x600dpi, f | 550 |
| SCX-4623F, fax cu laser, pagini de dimensiuni diverse, 22 ppm, max 1200x1200 dpi, scanner, USB, optional toner MLTD1052SELS, MLTD1052LELS | 849 |
| CLX-3175 16/4 ppm Color Laser Printer, 2400X600DPI, SPL, Scan Color 4800dpi, Copier 16/4ppm, FAX, USB 2.0, Direct USB, , Grey, 20.000 pages monthly duty cycle | 1,161 |
| BOXE | |
| Boxe GENIUS 1W RMS SP-5110 black, Volume, Headphones jack | 29 |
| Boxe Genius SP-5120 Black, 2W RMS, 120W PMPO, 230V EU | 47 |
| Boxe Genius 2.0 SP-700 Black, 16W, 1" tweeter x 2, line-in jack, headphone jack, 220V-EU, 31730922100 | 117 |
| Boxe GENIUS SW-2.1 355 Black, 10W(Subwoofer 5W+2 sateliti*2.5W), 355W PMPO, 220V-EU | 85 |
| Boxe 5.1 Genius SW-5.1 1505 Black, 47W(Subwoofer 17W+5 sateliti*6W), 1500W PMPO, 220V-EU, 31730934100 | 228 |
| Boxe 5.1 Genius SW-HF5.1 5050 Cherry(wood), LED Display-Volume, 150W(Subwoofer 75W+5 sateliti*15W), Telecoman | 504 |
| Boxe GENIUS 200W RMS SW-HF 5.1 6000 wood,Subwoofer: 100 watts,Satellites and Center: 20 watts each at THD10%, F | 703 |
| Logitech S120 2.0 2.3W RMS 2x1,15W/satelit - 50Hz - 20KHz Iesire casti, Control volum 2 ani | 46 |
| Logitech LS21 2.1 7W RMS 2x1,5W 4W 4 ohms - 1 kHz Subwoofer:3-inch (7.6 cm),Satellites: 2-inch (5.1 cm) high-exc | 121 |
| Logitech X-540 5.1 70W RMS 2 x 7.4W front, 15.4W centre, 2 x 7.4W rear 25W 40Hz - 20KHz 5.1 Surround Sound, mod | 431 |
| Boxe 2.1 Creative SBS A100, 4W+2x2W | 116 |
| Boxe 2.1 Creative Inspire A200, 5W+2x2W | 129 |
| Boxe 2.0 Hercules XPS 10 Gloss Black, 5W (2*2.5W) | 75 |
| RPC-275-2.1 2.1 Speakers 11W RMS (6W+2,5W*2) | 89 |
| RPC-221-5.1 5.1 Speakers 60W RMS (20W+8W*5) | 228 |

SERVICE CALCULATOARE

AVICENA COMPUTERS oferă clienților service în garanție și post-garanție pentru toate echipamentele comercializate

Specialistii nostri va ofera experienta celor 14 ani de service:

- Configurare și instalare de echipamente
- Intreținere și suport hardware/software
- Consultanță în probleme de hardware/software
- Soluții antivirus și de virusuri de sisteme
- Servicii de recuperare de date și sisteme
- Mutări, reinstalări și completări de configurații
- Service, curățări imprimante
- Configurare routere internet
- Instalări componente în sisteme desktop
- Service unitati LAPTOP / NOTEBOOK

REPARĂM POST GARANȚIE CALCULATOARE CUMPĂRATE DIN DIVERSE ALTE MAGAZINE

| INCARCARI CARTUSE INKJET | |
|--|----|
| INCARCARE INKJET BLACK 10ML a 5 -a încărcare este gratis ! | 10 |
| INCARCARE INKJET BLACK 20ML a 5 -a încărcare este gratis ! | 15 |
| INCARCARE INKJET BLACK 40-42ML a 5 -a încărcare este gratis ! | 21 |
| INCARCARE INKJET COLOR 10-11ML a 5 -a încărcare este gratis ! | 15 |
| INCARCARE INKJET COLOR 19-20-23ML a 5 -a încărcare este gratis ! | 20 |

Pentru detalii despre incarcari laser contactati serviciul tehnic Avicena.
Comercializam toata gama de consumabile pentru imprimante inkjet si laser.

PROGRAM:
LUNI – VINERI: 09.00 – 18.00
SAMBATA: 10.00 – 14.00